



NOTE:
 1. OUTER MOLDED WITH BLK PVC RESIN 887800019
 2. ALL COMPONENT MUST MEET RoHS REQUIREMENT.

J	COPPER FOIL	887801083		2
I	USB B REAL SHELL	887809082		1
H	USB B FRONT SHELL	887809081		1
G	HOUSING	887809085		1
F	TERMINAL	887809090 (AWG24)		4
E	TERMINAL	887809091 (AWG28)		4
D	USB 2.0 CABLE	#28x1P #24x2C ; 172000493	2M Ref.	1
C	USB A REAR SHELL	887809084		1
B	USB A FRONT SHELL	887809083		1
A	CRIMP HOUSING	887809086		1

SHELL	SHELL	SHIELDING	BRAID WIRE
4	4	GROUND	BLACK
3	3	+DATA	GREEN
2	2	-DATA	WHITE
1	1	VCC	RED
P 1	P 2	SIGNAL NAME	WIRE COLOR

ENTER DESCRIPTION EC NO: DG2006-0078 DRWN:PHZHU 2005/10/15 CHKD: 2005/10/19 APPR:DOLUO 2005/10/20	QUALITY SYMBOLS ▽=0 ◻=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
			mm	INCH	DRAWN BY PHZHU	DATE 2005/10/06	TITLE USB2.0 TYPE A/B BLK 6.6'		
		4 PLACES	± ---	± ---	CHECKED BY PHZHU	DATE 2005/10/06	MATERIAL NO. 68806-0004		
		3 PLACES	± ---	± ---	APPROVED BY ZXDENG	DATE 2005/10/06	DOCUMENT NO. SD-68806-004	SHEET NO. 1 OF 1	
2 PLACES	± ---	± ---	ANGULAR ±1/2°		MATERIAL NO. 68806-0004				
1 PLACE	± ---	± ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				