



SPECIFICATIONS								
WIRING	INPUT		OUTPUT			SHAFT ROTATION TO INCREASE VOLTAGE	TERMINAL CONNECTIONS FOR INCREASING VOLTAGE AS VIEWED FROM ROTOR END	
	VOLTS	HERTZ	VOLTS	MAX. AMPS	MAX. KVA		INPUT	OUTPUT
THREE PHASE OPEN DELTA	120	50/60	0-140	50	12.1	CW	2-1-2	3-1-3

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS #				UNITS		TITLE: SPEC. CONTROL DWG. VARIABLE TRANSFORMER TYPE: 5011CT-2D			
DECIMALS	Holes	ANGLES	DRAFT	IN	[mm]				
.XX, .XXX, .005	.002	1°	1-1/2°						
MATERIAL:				ALL DIMENSIONS APPLY AFTER PLATING		DRAWN BY: RAU DATE: 4/27/00 FIRST USED ON: DATE NOT SCALE DWG. CUSTOMER APPROVAL: DATE			
The information and design disclosed herein was originated by and is the property of STACO ENERGY PRODUCTS CO., which reserves all patent, proprietary, design, manufacturing, reproduction, use and sale rights thereto, and to any article disclosed therein except to the extent rights are expressly granted to others. The foregoing does not apply to vendor proprietary parts.						CHECKER: DATE:	WEIGHT APPROX. 134 LBS.	CODE IDENT. NO. 83008	
						ENGINEER: DATE:	SCALE .5=1	SHEET 1 OF 1	DWG. NO. 031-6016