



**Notes:**

1. Material and Finish:

- Protective Cover: Zinc Die-Cast, Nickel Plated
- Cover Gasket: Silicon, Color: White
- Ball Chain Assembly, Copper Alloy and Stainless steel, Nickel Plated

2. Operating Temperature: -40° C to +85° C

3. IP67 rated when fully mated with the appropriate connector

4. RoHS compliant

Directive 2002/95/EC RoHS Compliant

THIS DRAWING MAY NOT BE COPIED, OR REPRODUCED IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION <b>DO NOT ALTER CAD DRAWING BY HAND</b>	Customer:			Tolerance Unless otherwise specified			Scale: NTS	Dim. in mm	
	Name	Title	Approval Date	0 PLC ±0.50	1 PLC ±0.38		Material: See Notes		
				2 PLC ±0.25	3 PLC ±0.10	<b>Protective Cover Assembly Kit</b> with metal ball Chain Nickel Plated Zinc Die-Cast Version			
				ANGLES ±3°					
	d	1 x d	Mar/02/2011	Vincent ke	2009	Date	Name	Title	
c	3 x c	Dec/16/2010	Vincent ke	Draw.	Dec. 07	Vincent Ke	D-old		
b	1 x b	Jan/28/2010	Vincent ke	Appd.	Dec. 07	J. Chaudry	Drawing No.: 17K1A148		
a	original							Part No.: 17-101800	
Rev.	Changes	Date	Name					DIN A3	
								Sheet 1/1	

