

SCOPE: DUAL POWER MOSFET DRIVER

<u>Device Type</u>	<u>Generic Number</u>	<u>Circuit Function</u>
01	MAX4426M(x)/883B	Dual High-speed Inverting MOSFET Driver
02	MAX4427M(x)/883B	Dual High-speed Noninverting MOSFET Driver
03	MAX4428M(x)/883B	Dual High-speed Inverting/Noninverting MOSFET Driver

Case Outline(s). The case outlines shall be designated in Mil-Std-1835 and as follows:

<u>Outline Letter</u>	<u>Mil-Std-1835</u>	<u>Case Outline</u>	<u>Package Code</u>
JA	GDIP1-T8 or CDIP2-T8	8 LEAD CERDIP	J8
LP	CQCC1-N20	20 Leadless Carrier	LCC

Absolute Maximum Ratings

Supply Voltage V_{DD} to GND 20V
 Input Voltage $V_{DD} + 0.3V$ to GND $-0.3V$

Lead Temperature (soldering, 10 seconds) +300°C
 Storage Temperature -65°C to +150°C

Continuous Power Dissipation $T_A = +70^\circ C$
 8 pin CERDIP (derate 8.0mW/°C above +70°C) 640mW
 20 pin LCC (derate 9.1mW/°C above +70°C) 727mW
 Junction Temperature T_J +150°C
 Thermal Resistance, Junction to Case, θ_{JC}
 8 pin CERDIP 55°C/W
 20 pin LCC 20°C/W
 Thermal Resistance, Junction to Ambient, θ_{JA} :
 8 pin CERDIP 125°C/W
 20 pin LCC 110°C/W

Recommended Operating Conditions

Ambient Operating Range (T_A) -55°C to +125°C
 Supply Voltage Range $4.5V \leq V_{DD} \leq 18V$

	Package	ORDERING INFORMATION:
01	8 pin CERDIP	MAX4426MJA/883B
01	20 pin LCC	MAX4426MLP/883B
02	8 pin CERDIP	MAX4427MJA/883B
02	20 pin LCC	MAX4427MLP/883B
03	8 pin CERDIP	MAX4428MJA/883B
03	20 pin LCC	MAX4428MLP/883B

Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TABLE 1. ELECTRICAL TESTS:

TEST	Symbol	CONDITIONS	Group A Subgroup	Device type	Limits Min	Limits Max	Units
		-55 °C ≤ T _A ≤ +125 °C +4.5V ≤ V _{DD} ≤ 18V Unless otherwise specified					
Logic 1 Input Voltage	V _{IH}		1,2,3	All	2.4		V
Logic 0 Input Voltage	V _{IL}		1,2,3	All		0.8	V
Input Current	I _{IN}	V _{IN} = 0V to 18V	1,2,3	All	-1	1	μA
Output High Voltage	V _{OH}	No Load	1,2,3	All	V _{DD} -25		mV
Output Low Voltage	V _{OL}	No Load	1,2,3	All		25	mV
Output Resistance	R _{OUT}	V _{DD} =18V, I _{LOAD} =10mA, V _{IN} =0.8V for inverting stages, V _{IN} =2.4V for noninverting stages	1 2,3	All		10 12	Ω
Output Resistance	R _{OUT}	V _{DD} =18V, I _{OUT} =10mA, V _{IN} =0.8V for noninverting stages V _{IN} =2.4V for inverting stages	1 2,3	All		10 12	Ω
Power Supply Current	I _{S1}	V _{IN} =+3V, both inputs	1 2,3	01		4.5 8.0	mA
Power Supply Current	I _{S2}	V _{IN} =0V, both inputs	1 2,3	01		0.4 0.6	mA
Rise Time NOTE 1	t _r		9 10,11	All		30 40	ns
Fall Time NOTE 1	t _f		9 10,11	All		30 40	ns
Delay Time NOTE 1	t _{D1}		9 10,11	All		30 40	ns
Delay Time NOTE 1	t _{D2}		9 10,11	All		50 60	ns

NOTE 1: Guaranteed by design.

TERMINAL CONNECTIONS FOR 01, 02, 03.

8 PIN CERDIP				20 PIN LCC							
	01	02	03		01	02	03		01	02	03
1	NC	NC	NC	1	NC	NC	NC	11	NC	NC	NC
2	INA	INA	INA	2	NC	NC	NC	12	NC	NC	NC
3	GND	GND	GND	3	NC	NC	NC	13	NC	NC	NC
4	INB	INB	INB	4	INA	INA	INA	14	_____	OUTB	OUTB
5	_____	OUTB	OUTB	5	NC	NC	NC	15	NC	NC	NC
6	V _{DD}	V _{DD}	V _{DD}	6	GND	GND	GND	16	V _{DD}	V _{DD}	V _{DD}
7	_____	OUTA	_____	7	NC	NC	NC	17	NC	NC	NC
8	NC	NC	NC	8	INB	INB	INB	18	_____	OUTA	_____
				9	NC	NC	NC	19	NC	NC	NC
				10	NC	NC	NC	20	NC	NC	NC

QUALITY ASSURANCE

Sampling and inspection procedures shall be in accordance with MIL-Prf-38535, Appendix A as specified in Mil-Std-883.

Screening shall be in accordance with Method 5004 of Mil-Std-883. Burn-in test Method 1015:

1. Test Condition, A, B, C, or D.
2. TA = +125°C minimum.
3. Interim and final electrical test requirements shall be specified in Table 2.

Quality conformance inspection shall be in accordance with Method 5005 of Mil-Std-883, including Groups A, B, C, and D inspection.

Group A inspection:

1. Tests as specified in Table 2.
2. Selected subgroups in Table 1, Method 5005 of Mil-Std-883 shall be omitted.

Group C and D inspections:

- a. End-point electrical parameters shall be specified in Table 1.
- b. Steady-state life test, Method 1005 of Mil-Std-883:
 1. Test condition A, B, C, D.
 2. TA = +125°C, minimum.
 3. Test duration, 1000 hours, except as permitted by Method 1005 of Mil-Std-883.

TABLE 2. ELECTRICAL TEST REQUIREMENTS

Mil-Std-883 Test Requirements	Subgroups per Method 5005, Table 1
Interim Electric Parameters Method 5004	1
Final Electrical Parameters Method 5005	1*, 2, 3, 9, 10, 11
Group A Test Requirements Method 5005	1, 2, 3, 9, 10, 11
Group C and D End-Point Electrical Parameters Method 5005	1

* PDA applies to Subgroup 1 only.