

View on mating side

□	B	B	B	B	B	B	B	B	B	B	B	B	B	B
○	A	A	A	A	A	A	A	A	A	A	A	A	A	A

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪ ⑫ ⑬ ⑭ ⑮ ⑯ ⑰ ⑱ ⑲ ⑳ ㉑ ㉒ ㉓ ㉔ ㉕ ㉖ ㉗ ㉘ ㉙ ㉚ ㉛ ㉜ ㉝ ㉞ ㉟ ㊱ ㊲ ㊳ ㊴ ㊵ ㊶ ㊷ ㊸ ㊹ ㊺

A = 16 contacts L=2,8  
 B = 16 contacts L=2,8

S = 32 total number of contacts

Marking	Standard
Performance level	G1/0 = Contact area perform. level / Termination tin
Flux proof	yes
Fixing clip	no
Dimensions	SDA-85050-0002 sht.1
Technical Data	PS-85052-0001

B	G1/0	DRWG BY	KN	SIGN	
A	G1/0	CHK'D BY	Ca	SIGN	
Contact symbol	Perform. level	APP'D BY	JB	SIGN	
		SCALE			
		Contact position number			

ECN MC1998-2620	first release	97-10-17 KN
REVISIONS	FOR PREVIOUS REVISIONS SEE MRI LIST	
LTR	▷	

REVISE ONLY ON CAD SYSTEM	SH. REV.
CAD/CAM PROJECT NAME s8505001 s21	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
TITLE 32 pos. female connector acc. DIN 41612 style Q/2 contacts arrangement	SHEET NO. DATE 1 OF 1 97/10/17
MOLEX® MOLEX EUROPE	DWG NO. SD-85050-0127
PART NO. 85050-0127	SIZE A

