



**Features:**

- Motor: Shaded Pole Induction Motor
- Motor Protection: Impedance Protected
- Bearing Type: Two Ball
- Connection: UL 1430 AWG 22, 300mm Wire Leads or Terminal
- Frame Material: Aluminum Alloy
- Impeller Material: Plastic UL94V-0
- Operating Temp:  
Two Ball: -10°C~70°C
- Life Expectancy:  
Two Ball: 50,000 Hours



Fan-S Division



| Model No.          | Volt. | Freq. | Current   | Power       | Rated Speed | Maximum AirFlow |         | Maximum Static Pressure |               | Noise Level | Weight |
|--------------------|-------|-------|-----------|-------------|-------------|-----------------|---------|-------------------------|---------------|-------------|--------|
|                    | (VAC) | (Hz)  | (A)       | (W)         | (rpm)       | (CMM)           | (CFM)   | (InAq)                  | (mmAq)        | (dB/A)      | (g)    |
| FKA1-17251NBH** 31 | 115   | 50/60 | 0.55/0.46 | 62.10/51.80 | 2600/2700   | 4.867/5.348     | 172/189 | 0.433/0.408             | 10.998/10.363 | 55.5/57.7   | 1050   |
| FKA1-17251QBH** 31 | 230   | 50/60 | 0.27/0.23 | 59.80/50.60 | 2600/2700   | 4.867/5.348     | 172/189 | 0.433/0.408             | 10.998/10.363 | 55.5/57.7   | 1050   |
| FKA1-17251NBM** 31 | 115   | 50/60 | 0.33/0.31 | 36.80/34.50 | 2400/2300   | 4.528/3.962     | 160/140 | 0.340/0.180             | 8.636/4.572   | 53.0/50.3   | 1050   |
| FKA1-17251QBM** 31 | 230   | 50/60 | 0.17/0.17 | 36.80/36.80 | 2400/2300   | 4.528/3.962     | 160/140 | 0.340/0.180             | 8.636/4.572   | 53.0/50.3   | 1050   |

\*\* Indicates "W" (Wire Leads) or "T" (Terminal)

Noise is measured at the distance of one (1) meter from the axis of intake.

